



KISAN - KD20

CARACTERÍSTICAS TÉCNICAS

Velocidad de Procesamiento	300 billetes por minuto
Capacidad del alimentador	100 billetes
Capacidad de rechazo	100 billetes
Capacidad de bolsa / lienzo	Max. 10,000 billetes
Lectura de Número de Serie	Si
Funciones	Conteo por valor Rechazo billetes falsos y adulterados. Lectura de Soles y dólares
Detectar	Dual CIS, UV, MG, (18CH), IR, US
Conexiones	RS232C / LAN
Pantalla	LCD a color Táctil de 7"
Dimensiones	455 x 585 x 1.004 mm
Opciones	Tarjeta magnética. Tarjeta con chip IC. Lector de código de barras.
Seguridad de Bóveda	Acero de 2 mm.
Sistema de Anclaje	Cuatro puntos de anclaje en la base.
Impresora de Tickets	Impresora térmica incorporada.

KD20

High Speed Cash Deposit

KD20 as ideal front office and back office solution in the retail business, helps you safeguard assets against losses caused by human error and potential shrinkage.



FEATURES

1. High Speed Processing	<ul style="list-style-type: none"> · Up to 5 notes per sec · Time and cost saving for work efficiency · Proper in medium volume cash processing
2. High Performance Validator	<ul style="list-style-type: none"> · Based on recognition technology of banknote sorter · Detecting counterfeit notes with cash deposit
3. Easy Use	<ul style="list-style-type: none"> · Easy and simple UI · 4,000 notes or 10,000 notes Canvas Bag · Possibility of align with any equipment at any environment

SPECIFICATION

Model	KD20	
Dimensions (WxDxH)	Canvas bag (Small) 455x585x700mm	Canvas bag (Large) 455x585x1,004mm
Banknote inlet capacity	100 notes	
Banknote reject capacity	100 notes	
Feed direction	Short-edge first	
Transfer speed	300 notes per minute	
Banknote storage	Canvas bag (Small) 4,000 notes (per canvas bag)	Canvas bag (Large) 10,000 notes (per canvas bag)
Recognition unit	Counterfeit detection, serial number reading (OCR)	
Currencies	Available with up to 40 currencies	
Safe	2mm steel sheet, 8mm strong box	
Access	Front service	
Operator display	7 inches color touch panel	
Receipt printer	2" paper width	
Remote management	PC/KIOSK, Remote update	
Connections	USB, LAN	
Supply voltage range	AC 100V - AC 240V	
Options	User Identification: MSR/IC Card Reader, 2D barcode, NFC	
OS	Windows 10	

*Specification subject to change without notice.

DETAIL VIEW



ABOUT **KISAN**

KISAN ELECTRONICS



Web | www.kisane.com

Tel | +82-2-2204-7890

Fax | +82-2-2204-7899

E-mail | overseas@kisane.com

Add | 35, Seongsui-ro 20-gil, Seondong-gu, Seoul, Korea 04787